
## **CCT Dimming LED Panel light Specification**
















#### **Features**

- Choose high bright brand LED source panel, LM80 B10 standard, SDCM<3;
- ➤ Choose brand driver, such as Philips, Osram, Tridonic, LIFUD, etc;
- CCT 3000K, 4000K, 5000K, 6000K, precise to ±100K;
- > Triac, 1-10V, DALI, CCT dimming available to choose;
- Hanging, mounted, spring clips installation can choose;
- All product include materials strictly by CE, RoHS certificated

Application: Office, Conference&Meeting rooms, Supermarket, Shopping mall, Hotel, Hospital, Commercial Center etc.

### LED panel light raw material features




## **Parameter**

Input	DC24V	
Colour temp.	3000K-6000K dimming	
LM	110lm/W	
CRI	80	
LEDs	SMD2835	
LGP	PMMA	
Driver	No	
Dimming	CCT dimming	
UGR	21	
PF	0.90	
THD	<15	
Flicker	No	
Beam angle	120°	
Energy efficiency	A+	
IP grade	40	
Working temp.	-20°C ~ +40°C	


## **Item information**


Dimensions(mm)	Model No.	Support Power
595x295	AAPL-3060-20W-CCT	20-36W
1195x295	AAPL-3012-36W-CCT	20-40W
595x595	AAPL-6060-36W-CCT	20-40W
1195x595	AAPL-6012-60W-CCT	50-70W





## **Flexibility**

- Different dimming version available(Triac, 1-10V, DALI, CCT dimming)
- Emergency battery version available











# <u>Installation</u>


## -Recessed installation step



## -Hanging installation step



## -Mounted installation step



## -Spring clips installation step

