Data sheet NTT03

NTT03

24 Hour/7 Day Compact Electronic Immersion Heater Timeswitch

Features & Benefits

- 4 ON/4 OFF Programme Periods Per Day, Up To 28 ON/28 OFF Programmes Per Week
- Shortest Switching Time 1 Min
- Extra Large 'Easy View' Screen with Blue LED Backlighting
- Red LED 'Mains ON' and Green LED 'Output'
- Large Programme Buttons
- Self-Cancelling Override Button to Next Programme Change
- Optional 1 and 2 Hour Boost Button
- Automatic Summer/Winter Time Change
- Rechargeable Memory Back-Up
- Fits a Standard Flush or Surface Mount Box Min 32mm



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Ingress Protection Rating	IP20
Setting Type	Digital
Battery Type	NiMH 1.2V 80mAh Rechargeable Battery



	1
Power Reserve	672 Hours (28 Days)
Back Box Minimum Depth (mm)	32
Program Modes	24 Hour/7 Day, 1 Hour/2Hour Boost
Mounting Hole Centres (mm)	60
Standby Consumption	<0.96W
Number of Channels	1
Switch rating	16A Resistive , 2400W Halogen, 750W Fluorescent, 100W CFL, 100W LED
Shortest Switching Time	1 Minute
Programmable Slots	4 ON 4 OFF
Permanent ON Facility	Yes (Override ON)
Cable Capacity (mm2)	1.5 - 2.5mm ² Flexible Cable
Cable Entry(s)	Back Entry

General

Weight (g)	172
Height (mm)	92
Width (mm)	92
Depth (mm)	59
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483012314
Guarantee Period	3 Years
Trade Tariff Commodity Code	9032890090



Subject to technical changes and revisions

additional information at: https://www.timeguard.com This data was generated on

Line Diagrams





