



Features:

- Low Profile Constant Voltage Driver
- AC input: 220-240VAC
- Built in PFC Function, Flicker Free
- Efficiency up to 86%
- Protections: short circuit/ over loading/ over current/ over temperature
- Full protection plastic housing easy installation
- Cooling by free air convection
- Suitable for profile lighting and lightboxes

Models

ECP30-12VL

ECP30-24VL

Output Specifications

	ECP30-12VL	ECP30-24VL
Output Voltage	12V	24V
Voltage Tolerance	180mV	
Output Current	2.5A	1.25A
Rated Power	30W	

Input Specifications

Input Voltage	220-240VAC
Frequency Range	50-60Hz
Inrush Current	<20A
Full Load Efficiency (Typ.)	86%
AC Current (Max.)	0.17A
Power Factor	PF >0.9/230VAC (Full Loading)

Protection

Short Circuit	Shut down o/p voltage, re-power onto recover after fault condition is removed
Over Loading	<120%, Shut down o/p voltage, re-power onto recover
Over Temperature	115°C shut down o/p voltage, re-power onto recover
Protection Class	II

Environment

Working Temperature	-20~+45°C (Refer to derating curve), +80°C (max case temp.)
Working Humidity	10-90%

Safety & EMC

Safety standards	EN613471, EN61347-2-13
------------------	------------------------

Safety & EMC

EMS	EN61000-3-2; EN61000-3-3; EN61547
EMF	EN62493-2010
ERP	EN1194-2012

Other Specifications

IP Rating	IP20
Weight	0.14 Kg
Size	123 x 44.6 x 19.2 mm
Packing	255 x 205 x 160 mm (50PCS/CTN)

Mechanical Specifications

