

PRODUCT IMAGE



PRODUCT FEATURES

- 5050 4-in-1 LED
- 24V DC, 19.6W/M (0.49W/Inch)
- Silicon extrusion IP67
- Dimension: 22×12mm
- Side View: Bend direction horizontally
- Dot-free illumination
- Elegant appearance
- Color Changeable & Brightness Tunable
- Indoor and outdoor application

PRODUCT SPECIFICATIONS

LED Chip	5050 RGBW
IP	67
Maximum length	5M
Power Input	24V DC
Watt per meter	19.6W/M
LED Qty per meter	72LED/M
Dimension	22×12mm
Cuttable	83.33mm
Minimum bend Diameter	100mm
Material	Silicon
Operating Temperature Ranges	-20 to 45
Beam Angle	110°

SPECIFICATIONS TABLE

Model Number	wave length (nm)		Luminous Flux (lm/m)	PCB Width (mm)	Max.Length (m)	Min.Length (mm)	DC Voltage (V)	LED Qty. (PCS/M)	Rated Watt (W/M)	Rated Current (A/M)
FN1 RGBW	Red	620-630	/	12	5	83.33	DC24	72	19.6	0.81
	Green	515-530	/							
	Blue	460-470	/							
	WW	/	160							

DIMENSIONS

