


RGBW LED Panel light Specification



Features

- Choose high bright brand LED source panel, LM80 B10 standard, SDCM<3;
- CCT 3000K, 4000K, 5000K, 6000K, precise to $\pm 100\text{K}$;
- Touch remote control, switch control available to choose;
- Hanging, mounted, spring clips installation can choose;
- All product include materials strictly by CE, RoHS certificated

Application: Office, Conference&Meeting rooms, Supermarket, Shopping mall, Hotel, Hospital, Commercial Center etc.

LED panel light raw material features



Steel material frame

- 0.3mm thickness
- 850g net weight

EVA foam

- keep the LGP tightly to achieve
- a smoothly brightness

Mitsubishi acrylic(PMMA)


- light guide plate, best quality, no yellow

Diffuser plate

- A quality level, 1.5mm thickness,
- light transmittance 98%

Aluminum frame

- Net weight 435g (600x600mm)
- strong with good heat dissipation



LEDs

- Taiwan Epistar SMD5050+SMD2835
- High brightness, stable quality

PCB


- Heat dissipation coefficient 1.0

Parameter

Input	DC24V
Colour temp.	RGBW
Frame colour	White/silver
CRI	80
LEDs	SMD5050+SMD2835
LGP	PMMA
Driver	No
Dimming	No
UGR	21
PF	-
THD	-
Flicker	No
Beam angle	120°
Energy efficiency	A+
IP grade	40
Working temp.	-20°C ~ +40°C

Item information


Dimensions(mm)	Support Power
595x295	20-36W
1195x295	20-40W
595x595	20-40W
1195x595	50-60W




Flexibility

- Different dimming version available(Triac, 1-10V, DALI, CCT dimming)
- Emergency battery version available


Standard version




0-10V(1-10V) dimming version



Triac dimming version








with emergency kit version








Installation






-Recessed installation step



-Hanging installation step



-Mounted installation step



-Spring clips installation step

