FEELED DIVR 2 Spot





DIVA 2 Spot

Super Slim LED Recessed Spotlight! Perfect solution for kitchen cabinets, displays and furniture.








Various color



Single diode without multiple shadow





Product Features

- Linkable together and with Feelux Diva 2 linear LED
- Single 4W diode eliminates multiple shadows
- Virtually no heat emission and no UV radiation
- Available in silver, gold, white, black
- Friction fit in slim pocket with mounting spring option
- To be used with constant voltage DC 24V driver
- Dimmable with available accessories

Specification

- Voltage: DC 24V

Operating temperature : 0~45°CLamp life : 40,000hr/70%

- Available color: 3000K, 4000K, 6000K

Color rendering : Ra>80Energy efficiency : 75 lm/WDegree of protection IP20

- Total energy consumption of 4.3W


Max. connection of linked fixtures

- DIVA2 SPOT: Max 7pcs in a row

– LED Driver

Model Name	Max. units for Led driver			
	24V / 15W	24V / 30W	24V / 75W	
DVS4A4B24W	4	7	18	
DVS4B4B24W	4	7	18	

<u>Dimensio</u>n



Installation

Linkable between Diva2 Spot & Diva2 Spot (Type A)




Linkable between Diva2 Spot & Diva2 (Type A)



Linkable between Diva2 & Diva2 Spot (Type A)



End Unit (Type B)



Accessories

@ Diva2 spot linkable type						
White	Black	Gold	Silver			
DVS4A4B24W	DVS4A4B24B	DVS4A4B24G	DVS4A4B24S			
6 Diva2 spot end unit type						
White	Black	Gold	Silver			
DVS4B4B24W	DVS4B4B24B	DVS4B4B24G	DVS4B4B24S			

© Extension cable (Between Diva2 Spot & Diva2 Spot or 6 way distributor)

DVS cable(A): 2,500mm

d Connecting cable (Between Diva2 Spot & Diva2)

DVS cable(B): 1,000mm

@ connecting cable(Between Diva2 & Diva2 Spot)

NDVPC: 2500mm

① Dimming Controller (1-10V): FLD-V10

Mounting spring: DVS spring

h LED Driver with 6way distributor

Part No	FLC15-24V/T	FLC30-24V/T	FLC75-24V/ T
Capacity	15W 24V	30W 24V	75W 24V















