DecolanpT4 Linear Illumination



DecoLamp

DecoLamp offers a miniature lighting system with maximum flexibility. Its compact size fits even the narrowest spaces, while still providing excellent fluorescent lighting as sell as a striking appearance. The combination of miniautre T4 lamps with built-in electronic ballasts offers the very latest in lighting technology. Its high light-output and extremely low heat index make the DecoLamp ideal for a display cabinet, cove lighting and indirect lighting.



| Product Features

- Extremely low profile measuring 17mm width and 31.5mm height
- Cool operation ideal for heat-sensitive item display
- Rigid aluminum extruded body and snap-in mounting brackets
- Polycarbonate diffuser that gives off a soft glow

Benefits

- Minimum space requirement low energy consumption, high energy efficiency
- Instant-on starting, no flicker, long lamp life: 12,000hrs
- Ballast and lamp shut down if fault present
- Allows easy connection, reduces installation time
- Satisfy world class standard, TUV certified and UL listed

Application


- Remarkably low profile(T4 size 13mm) fits almost everywhere
- Kitchen, Cabinet, Showcase, Furniture

Notice

Max. connection: 270W

7W(38pcs), 10W(27pcs), 18W(15pcs)

Installation









Specification

Frequency range: 50/60HzVoltage: 220~240V, 110~130V

- Power factor: >97%
- Color rendering: Ra>80
- Tube life: 12,000hr
- Tube diameter: 13mm(T4)
- Class of protection II
- Degree of protection IP20

Accessories

	cables			
DLPTC/T	DLPTC1/T	DLPTC2/T	DLPTC4/T	DLPTC6/T
150mm(6inch)	300mm(1feet)	600mm(2feet)	1200mm(4feet)	1800mm(6feet)

b Direct connector : DLCPL/T

© Power cord

DLPC230/T

DLPC230/SM2/T (Straight type)

@ Diffuser

DL7CV	DL10CV	DL18CV				
7W	10W	18W				

Mounting Bracket

f Fluorescent lamps

3000K, 4000K, 5500K, 6500K, 8000K, Red, Green and Blue are available.

⑨ On/Off switch : DLSB/T

Model Name	Lamp (W)	lm	Input (mA)	L(mm)	W(mm)	H(mm)	H(mm) with diffuse
DL7A4B23NC/T	7	420	58	262	17	31.5	33
DL10A4B23NC/T	10	700	83	339	17	31.5	33
DL18A4B23NC/T	18	1305	150	517	17	31.5	33

















