


DIMMABLE Glass GU10 LED 5W

April 2013 PART L residential-commercial





The GU10 LED 6W is a 5W LED lamp designed to fit in any GU10 lampholder. The GU10 LED 5W is fully dimmable with all leading edge dimmers (we recommend against trailing edge) and also complies with the April 2013 Part L Regulations.

Key Features

- · Complies with April 2013 Part L regulations
 - L1A New dwellings
 - L1B Existing Dwellings
 - L2A New Buildings other than Dwellings
 - L2B Existing Buildings other than dwellings
- Fully dimmable with leading edge dimmers
- Equivalent to 50W GU10
- Lifetime of 25,000hrs (3 years)
- Fits GU10 lampholder

Specification

Сар	GU10
Length	54mm
Diameter	50mm
Wattage	5W
Voltage	240V
Colour Temp	3000k
CRI	80
Lumen	400
Lumen per Watt W/W	67
Beam Angles	35°
Power Factor	0.62

Test Report for GU10 LED 5W Dimmable

Manufacturer	Product Code	Wattage	LED Bulb Min Quantity	LED Bulb Max Quantity
Aton	IDIMP4	60-400W	1	20
Danlers	DPD250	60-250W	1	20
Danlers	DPD400	60-400W	1	20
Danlers	DPD_LED250	5-250W	1	20
Lutron	LUTRON RANIA	50-450W	5	20
Lutron	LUTRON GRAFIK EYE 3000	40-800W	1	20
Lutron	LUTRON GRAFIK EYE QS	40-500W	1	20
SWITCH TO WOOD	V-Pro	10-400W	1	20
LE	6TEP400 ROTARY	5-400W	1	20
Focus SB	SB-DSP400	60-400W	1	20
Zano	ZGRID500	50-500W	1	20
TELECO	WISE FUSIONREC1B 450W	450W	9	20
Hamiliton	LK400/2	40-400W	10	20

*Where a minmum load is required, please use the recommended items within the brackets in the section above.

The above list of dimmers have been tested with the GU10 LED 5W. Please speak to your supplier if you would like your dimmer added to our testing list.

Available Lamps

Product Code	Angle	Temp	Lumens	lm/W	Life
GU10 LED 5W 36D W/W	35°	W/W 3000k	400	80	25000hrs

Light Cone Data

GU10 LED 5W 3000k/ 35D Lux at a Distance

	■■ 量測角度: CO-C360		
1m	680.49 lux		64cm
2m	170.12 lux		128cm
3m	75.61 lux		193cm
4m	42.53 lux		257cm
5m	27.22 lux		321cm
6m	18.90 lux		385cm
7m	13.89 lux		449cm
8m	10.63 lux		513cm
9m	8.40 lux		578cm
10m	6.80 lux		642cm

35°

