ledunited * * *

REALITY DIMMABLE PAR30 LED 12W LAMP 2013 PART L



0.90

residential-commercial

The PAR30 LED 12W is a 12W LED lamp designed to fit in any PAR30 lampholder. The PAR30 LED 12W is fully dimmable with all **leading edge** dimmers (we recommend against trailing edge) and also complies with the 2013 Part L Regulations.

Key Features	Specification				
•	Length	91mm			
Complies with 2013 Part L regulations	Diameter	94.5mm			
L1A New dwellings	Weight	165g			
L1B Existing Dwellings L2A New Buildings other than Dwellings	Wattage	12W			
L2B Existing Buildings other than dwellings	Voltage	240V			
Fully dimmable with leading edge dimmers	Colour Temp	2700k / 3000k			
Facility along the DADOO 75W/ Helenen	CRI	90			
Equivalent to PAR30 75W Halogen	Lumen	850 lm / 850lm			
Lifetime of 25,000hrs	Lumen per Watt	71lm/W / 71lm/W			
•	Beam Angles	35°			

Test Report for PAR30 LED 12W LAMP Dimmable

Power Factor

Manufacturer	Product Name	Product Code	Wattage		ED Bulb Quantity
ATON	2 Way 400W Push Dimmer Module	IDIMP400	4-400W	NO	120
ATON	2 Way 1000W Push Dimmer Module	IDIMP1000	10-1000W	NO	120
DANLERS	2 Way 250W Push Dimmer Module	DPD250W	40-250W	NO	210
DANLERS	2 Way 400W Push Dimmer Module	DPD400W	60-400W	NO	210
FOCUS SB	2 Way 400W Push Dimmer Module	SB-DSP400X	60-400W	NO	120
LUTRON	Rania 1 Gang 450W Master Dimmer	RNSU-452B	50-450W	NO	220
LUTRON	Lyneo 1 Gang 500W Dimmer	LLSI-502B	40-500W	NO	120
LUTRON	Grafik Eye QS 4 Circuit 500W Dimmer	QSGRK-4PCE	40-500W	NO	120
LUTRON	Grafik Eye 4 Circuit 800W Dimmer	GRX3104TCE	40-800W	NO	120
MK	2 Way 450W Push Dimmer	MK1535 WHITE	65-450W	NO	120
RAKO	Trailing Edge 500W Dimming Pack	RDT500-C	1-500W	NO	120
SUPERSWITCH	2 Way 250W Push Dimmer	WHDSW1 250W	40-250W	NO	116
WISE CONTROLS	Fusion 1 Gang 450W Dimmer	WISE FUSIONREC1	25-450W	NO - Must use LED Mode	220
WISE CONTROLS	Scene/Dimming Receiver 1 Circuit 500W	WISESCENE DIM	25-500W	NO	120
WISE CONTROLS	Scene/Dimming Receiver 1 Circuit 250W	WISESCENE OCTO	25-250W	NO - Must use LED Mode	216
WISE CONTROLS	Dimming Receiver 4 Channel 700W	WISEDIMREC BOX	60-700W	NO	120
ZANO	500W(T)400W(VA)66W(CFL)50W(LED)	ZGRID500	40-500W	NO	120
MK	230V 50Hz 40W/VA-200W/180VA	K4501	40-220W	NO	120

The above list of dimmers have been tested with the PAR30 LED 12W. Please speak to your supplier if you would like your dimmer added to our testing list.

Available Lamps

Product Code	Angle	Temp	Lumens	lm/W	Life
PAR30 LED 12W 35D W/W	35°	W/W 2700k	850	71	25000hrs
PAR30 LED 12W 35D W/W	35°	W/W 3000k	850	71	25000hrs

Light Cone Data

PAR30 LED 12W 2700K/3000k 35D

Lux at a Distance

[Testing Angle: C0-C360				
1m	4251.54 lux				36cm
2m	1062.89 lux				71cm
3m	472.39 lux				107cm
4m	265.72 lux				142cm
5m	170.06 lux				178cm
6m	118.10 lux				213cm
7m	86.77 lux		N		249cm
8m	66.43 lux				285cm
9m	52.49 lux				320cm
10m	42.52 lux			N	356cm

Beam Angle: 35°

