Ledunited★ ★ ★ REALITY DIMMABLE MR11 LED 3.5W LAMP

OCT 2010 PART L

residential-commercial



- The MR11 LED 3.5W is a 3.5W LED lamp designed to fit in any MR11 lampholder. The MR11 LED 3.5W is fully dimmable with all **leading edge** dimmers (we recommend against trailing edge) and also complies with the October 2010 Part L Regulations.
- Only USE The LED Driver (Model: GY3.5WX1).

Key Features

- Complies with October 2010 Part L regulations
 - L1A New dwellings
 - L1B Existing Dwellings
 - L2A New Buildings other than Dwellings
 - L2B Existing Buildings other than dwellings
- Fully dimmable with leading edge dimmers
- Equivalent to 35W GU10
- Lifetime of 25,000hrs
- Fits MR11 lampholder

LED Driver(Model:GY3.5WX1) Specification

Input Voltage 240Vac

Output 36Vdc 70mA Max

Wattage 3.5W Power Factor 0.90 IP Rating IP20

Case size (length*width*thickness) 71mm*25mm*23mm

The MR11 LED 3.5W Bulb Specification

- 1. CITIZEN LED
- Warm White 2700K 320Im CRI 80 91 Im/W
- 3. Reflecting cup Angle: 35°
- 4. Input: 36Vdc 70mA Max
- 5. No polarity
- 6. Dimension: Diameter 34.5mm MAX High 36.5mm MAX

Test Report for MR11 LED 3.5W Dimmable

Manufacturer	Product Name	Product Code	Wattage		D Bulb
ATON	2 Way 400W Push Dimmer Module	IDIMP400	4-400W	NO	uantity 120
ATON	2 Way 1000W Push Dimmer Module	IDIMP1000	10-1000W	NO	120
DANLERS	2 Way 250W Push Dimmer Module	DPD250W	40-250W	NO	120
DANLERS	2 Way 400W Push Dimmer Module	DPD400W	40-230W 60-400W	NO	120
FOCUS SB	2 Way 400W Push Dimmer Module	SB-DSP400X	60-400W	NO	120
LUTRON	Rania 1 Gang 450W Master Dimmer	RNSU-452B			
LUTRON	Lyneo 1 Gang 500W Dimmer		50-450W	NO	220
LUTRON	Grafik Eye QS 4 Circuit 500W Dimmer	LLSI-502B	40-500W	NO	220
	· · · · · · · · · · · · · · · · · · ·	QSGRK-4PCE	40-500W	NO	120
LUTRON	Grafik Eye 4 Circuit 800W Dimmer	GRX3104TCE	40-800W	NO	120
MK	2 Way 450W Push Dimmer	MK1535 WHITE	65-450W	NO	220
RAKO	Trailing Edge 500W Dimming Pack	RDT500-C	1-500W	NO	120
SUPERSWITCH	2 Way 250W Push Dimmer	WHDSW1 250W	40-250W	NO	120
WISE CONTROLS	Fusion 1 Gang 450W Dimmer	WISE FUSIONREC1	25-450W	NO - Must use LED Mode	420
WISE CONTROLS	Scene/Dimming Receiver 1 Circuit 500W	WISESCENE DIM	25-500W	NO	520
WISE CONTROLS	Scene/Dimming Receiver 1 Circuit 250W	WISESCENE OCTO	25-250W	NO - Must use LED Mode	320
WISE CONTROLS	Dimming Receiver 4 Channel 700W	WISEDIMREC BOX	60-700W	NO	120
ZANO	500W(T)400W(VA)66W(CFL)50W(LED)	ZGRID500	40-500W	NO	120
MK	230V 50Hz 40W/VA-200W/180VA	K4501	40-220W	NO	120

*Where a minmum load is required, please use the recommended items within the brackets in the section above.

The above list of dimmers have been tested with the MR11 LED 3.5W. Please speak to your supplier if you would like your dimmer added to our testing list.

Available Lamps

Product Code	Angle	Temp	Lumens	lm/W	Life
MR11 LED 3.5W 35D W/W	35°	W/W 2700k	320	91	25000hrs

Light Cone Data

Warm White

MR11 LED 3.5W 2700K 35D Lux at a Distance

1m	827.92 lux			46cm
2m	206.98 lux	1		92cm
3m	91.99 lux			137cm
4m	51.75 lux			183cm
5m	33.12 lux			229cm
6m	23.00 lux			275cm
7m	16.90 lux			321cm
8m	12.94 lux			366cm
9m	10.22 lux			412cm
10m	8.28 lux			458cm

Beam Angle: 35°

