

Test report for compatible dimmers

Manufacturer	Product Code	Wattage	Min Load Required
ATON	IDIMP4	60-400W	NO
ATON	IDIMP400	4-400W	NO
ATON	IDIMP1000	10-1000W	NO
DANLERS	DPD250W	40-250W	NO
DANLERS	DPD400W	60-400W	NO
FOCUS SB	SB-DSP400X	60-400W	NO
LUTRON	LYNEO LLSI-502B	40-500W	NO
LUTRON	LUTRON GRAFIX EYE QS	40-500W	NO
MK	MK1535 WHITE	65-450W	NO
MK	K4501	40-220W	NO
RAKO	RAKO RDL250	40-250W	NO
RAKO	RAKO RDT500-C	1-500W	NO
SUPERSWITCH	WHDSW1 250W	40-250W	NO
WISE CONTROLS	WISESCENE DIM	25-500W	NO
WISE CONTROLS	WISEDIMREC BOX	60-700W	NO
ZANO	ZGRID500	40-500W	NO
Hamilton	LITESTAT 40-400W	40-400W	NO
Powersave lighting	Powersave lighting 5-500VA	5-500W	NO
MEM	MEM250W	40-250W	NO

Light Cone Data

Lux at a Distance 2700k

1m	1233.09 lux	44cm
2m	308.27 lux	89cm
3m	137.01 lux	133cm
4m	77.07 lux	177cm
5m	49.32 lux	222cm
6m	34.25 lux	266cm
7m	25.17 lux	311cm
8m	19.27 lux	355cm
9m	15.22 lux	399cm
10m	12.33 lux	444cm

Beam Angle : 35°